

Medical gas devices



Oxygen dispenser splitter 0-15 l/min

Product description

Trigger flowmeters are instantaneous dispensers used to deliver medical gases in oxygen therapy; the flow rate is guaranteed by calibrated orifices; due to their ergonomic design and ease of use, they are also suitable for heavy-duty use and on emergency and rescue vehicles.

Normatives

NF S 90-116 | UNI 9507 | UNI EN ISO 15002 | DIN 13260-2 | BS 5682 | SS 8752430

Components

- Chemically nickel-plated brass body.
- AISI 316 stainless steel diaphragm with calibrated holes.
- Inlet with specific gas coupling or G 1/4" M RIGHT thread.
- Outlet threaded G 1/4" M RIGHT or M12x1.25 M RIGHT.
- ABS click adjustment knob.
- EPDM and silicone O-ring seal.

Technical data

CODE	GAS	INLET CONNECTION	OUTLET CONNECTION	SCALE	BAR
HD259	O ₂	UNI 9507	G 1/4" M	0-15 l/min	4,5
HD260	O ₂	AFNOR NF S 90-116	G 1/4" M	0-15 l/min	4,5
HD261	O ₂	DIN 13260-2	G 1/4" M	0-15 l/min	4,5
HD262	O ₂	BS 5682	G 1/4" M	0-15 l/min	4,5
HD263	O ₂	SS 8752430	G 1/4" M	0-15 l/min	4,5
HD330	O ₂	AFNOR NF S 90-116	M12x1,25 M	0-15 l/min	4,5
HD379	O ₂	UNI 9507	9/16" UNF M	0-15 l/min	4,5
HD380	O ₂	AFNOR NF S 90-116	9/16" UNF M	0-15 l/min	4,5
HD381	O ₂	DIN 13260-2	9/16" UNF M	0-15 l/min	4,5

Technical data

CODE	GAS	INLET CONNECTION	OUTLET CONNECTION	SCALE	BAR
HD382	O ₂	BS 5682	9/16" UNF M	0-15 l/min	4,5
HD383	O ₂	SS 8752430	9/16" UNF M	0-15 l/min	4,5

Behringer S.r.l. via Gualco 4, 16165 Genova ITALY

T +39 010 8309103 **F** +39 010 8309183 **e-mail** info@behringer.it **C.F. e P.I.** 01167840998