



# Flaming devices



## AIR TECNO control unit - ATEX

### Product description

The gas regulator and decompression control unit is installed near the flaming machine. The control unit has two 451 low pressure reducers, one for the oxygen line and one for the propane line, as well as four air pressure operated valves which, with the M0093 "AIR TECNO" electronic control box control the pilot flame, main flame and torch cooling water.

### Maintenance kit

CODE	SPARES
M0002	CONTROL UNIT FILTER - O <sub>2</sub>
M0002A	CONTROL UNIT FILTER - C <sub>3</sub> H <sub>8</sub>
M0002B	CONTROL UNIT FILTER - H <sub>2</sub> O
C7339	REDUCER 451 - O <sub>2</sub>
C7359	REDUCER 451 - C <sub>3</sub> H <sub>8</sub>
HM059	0-2.5 bar PRESSURE GAUGE
HM060	0-16 bar PRESSURE GAUGE
HM061	0-40 bar PRESSURE GAUGE
C0670	AIR PRESSURE OPERATED VALVE

### Technical data

CODE	OXYGEN P <sub>1</sub> max.	OXYGEN P <sub>2</sub>	PROPANE P <sub>1</sub> max.	PROPANE P <sub>2</sub>
M0080	30 bar	2 - 5,5 bar	4 bar	0,5 - 1,2 bar