



Automatic flaming nozzles

Product description



The automatic flaming nozzles are used in automatic flaming and can be installed on either the BS/86 torch or the LITTLE/F torch. BS/P nozzles produce a single flame, and must have a special fixing ring nut (C0358) to be installed on automatic flaming torches.

Components

ACCESSORIES	CODE
BSP RING NUT	C0358
BS/P1-1.5 MIXER	M0043AC
BS/P2-4 MIXER	M0043

Technical data

CODE	NOZZLES	TORCH	P O ₂	Q O ₂	P C ₃ H ₈	Q C ₃ H ₈
M0042A	BS/P1	BS/86	2 bar	1,2 Nm ³ /h	1,2 bar	0,2 Nm ³ /h
		LITTLE/F	3 bar	1 Nm ³ /h	1,2 bar	0,2 Nm ³ /h
M0042B	BS/P1,5	BS/86	2 bar	1,3 Nm ³ /h	1,2 bar	0,3 Nm ³ /h
		LITTLE/F	3 bar	1,4 Nm ³ /h	1,2 bar	0,4 Nm ³ /h
M0042	BS/P2	BS/86	5,5 bar	11,3 Nm ³ /h	1,2 bar	1,4 Nm ³ /h
		LITTLE/F	5,5 bar	11,15 Nm ³ /h	1,2 bar	2 Nm ³ /h
M0041A	BS/P3	BS/86	5,5 bar	11,4 Nm ³ /h	1,2 bar	1,9 Nm ³ /h
		LITTLE/F	5,5 bar	11,6 Nm ³ /h	1,2 bar	2,4 Nm ³ /h
M0041	BS/P4	BS/86	5,5 bar	13,9 Nm ³ /h	1,2 bar	3,1 Nm ³ /h
		LITTLE/F	5,5 bar	12 Nm ³ /h	1,2 bar	2,2 Nm ³ /h