



High Pressure flexible inox connection

CE
Organismo Notificato n. 0476
Notified Body nr. 0476

Product description

Flexible connection for high pressure made with double stainless steel tights and specific gas connections for the High Pressure connection of the cylinder to the manifold or to the central panel; inox gas specific connections according each country standard; available in lengths of 1 or 2 meters; complete with adjustable safety inox cable.

Normatives

UNI EN ISO 7396-1 | ISO 5145 | UNI EN ISO 21969 | UNI EN ISO 15001

Components

Flexible metal hose with parallel coils in AISI 316, with two reinforcement braids in AISI 304.
Fittings and connections, both sides, in AISI 316.
Anti-tilt stainless steel cable 1 meter longer than the flexible one.

Technical data

CODE	GAS	LENGTH	INLET - OUTLET CONNECTIONS	P. MAX
HS077MT1N02	O_2 (D)	1 m.	DIN-9 -> UNI-2	200 bar
HS077MT1N03	O_2 (BS)	1 m.	BS-3 -> UNI-2	200 bar
HS077MT1N04	O_2 (CAH)	1 m.	NF-F -> CAH	200 bar
HS077MT1N05	O_2 (F-IND)	1 m.	NF-F -> UNI-2	200 bar
HS077MT1N06	O_2 (CGA540)	1 m.	CGA540 -> UNI-2	200 bar
HS077MT1N10	Air (D)	1 m.	DIN-13 -> UNI-6	200 bar
HS077MT1N11	Air (BS)	1 m.	BS-3 -> UNI-6	200 bar
HS077MT1N12	Air (F)-CAHOUET TYPE C	1 m.	NF-D -> CAH	200 bar
HS077MT1N13	Air (TYPE F)	1 m.	NF-D -> UNI-6	200 bar
HS077MT1N14	Air (CGA)	1 m.	CGA346 -> UNI-6	200 bar
HS077MT1N16	Air (IND)	1 m.	NF-F -> UNI-6	200 bar
HS077MT1N17	N_2O (I-D)	1 m.	UNI-9-DIN-11 -> UNI-9-DIN-11	200 bar

Behringer S.r.l. via Gualco 4, 16165 Genova ITALY
T +39 010 8309103 **F** +39 010 8309183 **e-mail** info@behringer.it **C.F.** e **P.I.** 01167840998

Technical data

CODE	GAS	LENGTH	INLET - OUTLET CONNECTIONS	P. MAX
HS077MT1N19	N_2O (BS)	1 m.	BS-13 -> UNI-9-DIN-11	200 bar
HS077MT1N20	N_2O (F)-CAHOUET TYPE C	1 m.	NF-G -> CAH	200 bar
HS077MT1N21	N_2O (TYPE F)	1 m.	NF-G -> UNI-9-DIN-11	200 bar
HS077MT1N22	N_2O (CGA)	1 m.	CGA326 -> UNI-9-DIN-11	200 bar
HS077MT1N24	N_2O (IND)	1 m.	NF-F -> UNI-9-DIN-11	200 bar
HS077MT1N26	N_2 (D)	1 m.	DIN-10 -> UNI-5	200 bar
HS077MT1N27	N_2 (BS)	1 m.	BS-3 -> UNI-5	200 bar
HS077MT1N28	N_2 (F)-CAHOUET TYPE C	1 m.	NF-C -> CAH	200 bar
HS077MT1N29	N_2 (TYPE F)	1 m.	NF-C -> UNI-5	200 bar
HS077MT1N30	N_2 (CGA)	1 m.	CGA580 -> UNI-5	200 bar
HS077MT1N32	N_2 (IND)	1 m.	NF-F -> UNI-5	200 bar
HS077MT1N34	CO_2 (D)	1 m.	DIN-6 -> UNI-10	200 bar
HS077MT1N35	CO_2 (BS)	1 m.	BS-8 -> UNI-10	200 bar
HS077MT1N36	CO_2 (F)-CAHOUET TYPE C	1 m.	NF-C -> CAH	200 bar
HS077MT1N37	CO_2 (TYPE F)	1 m.	NF-C -> UNI-10	200 bar
HS077MT1N38	CO_2 (CGA)	1 m.	CGA320 -> UNI-10	200 bar
HS077MT1N40	CO_2 (IND)	1 m.	NF-F -> UNI-10	200 bar
HS077MT2N02	O_2 (D)	2 m.	DIN-9 -> UNI-2	200 bar
HS077MT2N03	O_2 (BS)	2 m.	BS-3 -> UNI-2	200 bar
HS077MT2N04	O_2 (F)-CAHOUET TYPE C	2 m.	NF-F -> CAH	200 bar
HS077MT2N05	O_2 (TYPE F)	2 m.	NF-F -> UNI-2	200 bar
HS077MT2N06	O_2 (CGA)	2 m.	CGA540 -> UNI-2	200 bar
HS077MT2N10	Air (D)	2 m.	DIN-13 -> UNI-6	200 bar
HS077MT2N11	Air (BS)	2 m.	BS-3 -> UNI-6	200 bar
HS077MT2N12	Air (F)-CAHOUET TYPE C	2 m.	NF-D -> CAH	200 bar
HS077MT2N13	Air - TYPE F	2 m.	NF-D -> UNI-6	200 bar
HS077MT2N14	Air - CGA	2 m.	CGA346 -> UNI-6	200 bar
HS077MT2N16	Air - IND	2 m.	NF-F -> UNI-6	200 bar
HS077MT2N17	N_2O (I-D)	2 m.	UNI-9-DIN-11 -> UNI-9-DIN-11	200 bar
HS077MT2N19	N_2O (BS)	2 m.	BS-13 -> UNI-9-DIN-11	200 bar
HS077MT2N20	N_2O (F)-CAHOUET TYPE C	2 m.	NF-G -> CAH	200 bar
HS077MT2N21	N_2O - TYPE F	2 m.	NF-G -> UNI-9-DIN-11	200 bar
HS077MT2N22	N_2O - CGA	2 m.	CGA326 -> UNI-9-DIN-11	200 bar
HS077MT2N24	N_2O - IND	2 m.	NF-F -> UNI-9-DIN-11	200 bar
HS077MT2N26	N_2 (D)	2 m.	DIN-10 -> UNI-5	200 bar
HS077MT2N27	N_2 (BS)	2 m.	BS-3 -> UNI-5	200 bar
HS077MT2N28	N_2 (F)-CAHOUET TYPE C	2 m.	NF-C -> CAH	200 bar
HS077MT2N29	N_2 (TYPE F)	2 m.	NF-C -> UNI-5	200 bar
HS077MT2N30	N_2 (CGA)	2 m.	CGA580 -> UNI-5	200 bar
HS077MT2N32	N_2 (IND)	2 m.	NF-F -> UNI-5	200 bar
HS077MT2N34	CO_2 (D)	2 m.	DIN-6 -> UNI-10	200 bar
HS077MT2N35	CO_2 (BS)	2 m.	BS-8 -> UNI-10	200 bar

Behringer S.r.l. via Gualco 4, 16165 Genova ITALY

T +39 010 8309103 **F** +39 010 8309183 **e-mail** info@behringer.it **C.F.** e **P.I.** 01167840998

Technical data

CODE	GAS	LENGTH	INLET - OUTLET CONNECTIONS	P. MAX
HS077MT2N36	CO_2 (F)-CAHOUET TYPE C	2 m.	NF-C -> CAH	200 bar
HS077MT2N37	CO_2 (TYPE F)	2 m.	NF-C -> UNI-10	200 bar
HS077MT2N38	CO_2 (CGA)	2 m.	CGA320 -> UNI-10	200 bar
HS077MT2N40	CO_2 (IND)	2 m.	NF-F -> UNI-10	200 bar

Behringer S.r.l. via Gualco 4, 16165 Genova ITALY
T +39 010 8309103 **F** +39 010 8309183 **e-mail** info@behringer.it **C.F.** e **P.I.** 01167840998