



Medical gas devices



Ramp/ramp copper connection

Product description

Copper connection fitting for connecting two high pressure ramps or at the inlet of the decompression panel. The swivel nuts are gas specific threads in accordance with the standards.



Organismo Notificato n. 0476
Notified Body nr. 0476

Normatives

UNI EN ISO 7396-1 | ISO 5145 | UNI EN ISO 21969 | UNI EN ISO 15001 | UNI 11144

Components

High pressure nickel-plated copper pipe with external diameter Ø 10 mm, internal diameter Ø 5 mm. Brass inlet and outlet connectors with specific threading and seal according to the gas.

Technical data

CODE	GAS	LENGTH	CONNECTION	WEIGHT	P.MAX
HS097	O ₂	0,65 m	UNI-2 -> UNI-2	0.75 kg	200 bar
HS098	N ₂ O	0,65 m	UNI-9-DIN-11 -> UNI-9-DIN-11	0.75 kg	200 bar
HS099	N ₂	0,65 m	UNI-5 -> UNI-5	0.75 kg	200 bar
HS100	CO ₂	0,65 m	UNI-10 -> UNI-10	0.75 kg	200 bar
HS101	Air	0,65 m	UNI-6 -> UNI-6	0.75 kg	200 bar