



LEM lances

Product description

LEM oxyacetylene welding lances to be used with the LEM/S universal grip (code M0007).

Normatives

UNI EN ISO 9539 | UNI EN ISO 5172

Maintenance kit

| CODE | SPARES |
|-------|-----------------------|
| C0473 | MEC/LEM LANCE TIP N.0 |
| C0474 | MEC/LEM LANCE TIP N.1 |
| C0475 | MEC/LEM LANCE TIP N.2 |
| C0476 | MEC/LEM LANCE TIP N.3 |
| C0477 | MEC/LEM LANCE TIP N.4 |
| C0478 | MEC/LEM LANCE TIP N.5 |
| C0479 | MEC/LEM LANCE TIP N.6 |
| C0480 | MEC/LEM LANCE TIP N.7 |

Technical data

| CODE | P O ₂ | Q O ₂ | P C ₂ H ₂ | Q C ₂ H ₂ | LENGTH | WEIGHT |
|--------|------------------|------------------------|---------------------------------|---------------------------------|--------|---------|
| C3002L | 4,5 bar | 1,2 Nm ³ /h | 1,2 bar | 0,3 Nm ³ /h | 200 mm | 0,18 kg |
| C3003L | 4,5 bar | 1,4 Nm ³ /h | 1,2 bar | 0,3 Nm ³ /h | 230 mm | 0,19 kg |
| C3004L | 4,5 bar | 1,9 Nm ³ /h | 1,2 bar | 0,3 Nm ³ /h | 260 mm | 0,2 kg |
| C3005L | 4,5 bar | 1,2 Nm ³ /h | 1,2 bar | 0,3 Nm ³ /h | 290 mm | 0,21 kg |
| C3006L | 4,5 bar | 1,4 Nm ³ /h | 1,2 bar | 0,3 Nm ³ /h | 315 mm | 0,28 kg |
| C3007L | 4,5 bar | 1,9 Nm ³ /h | 1,2 bar | 0,3 Nm ³ /h | 345 mm | 0,3 kg |

Technical data

| CODE | P O ₂ | Q O ₂ | P C ₂ H ₂ | Q C ₂ H ₂ | LENGTH | WEIGHT |
|--------|------------------|------------------------|---------------------------------|---------------------------------|--------|---------|
| C3008L | 4,5 bar | 1,4 Nm ³ /h | 1,2 bar | 0,3 Nm ³ /h | 365 mm | 0,31 kg |
| C3009L | 4,5 bar | 1,9 Nm ³ /h | 1,2 bar | 0,3 Nm ³ /h | 395 mm | 0,46 kg |

Behringer S.r.l. via Gualco 4, 16165 Genova ITALY

T +39 010 8309103 **F** +39 010 8309183 **e-mail** info@behringer.it **C.F. e P.I.** 01167840998