



## Rail Double flowmeter 0-15 l/min

### Product description

Double variable area flow meter for doubling the single usage, available with 0-15 l/min flow meter; it can be connected to the network by means of couplings AFNOR NF S 90-116, DIN 13260-1, UNI 9507, BS 5682, G thread 1/4" M RH; also available with ABS clamp for instrument bar with specific gas connection; the device enables, by adjusting the needle valve, a flow ranging from 0 to 15 at a pressure of 4.5 bar; flow meter outlet G 1/4" M RH or 9/16".



### Normatives

UNI EN ISO 9539 | NF S 90-116 | UNI 9507 | UNI EN ISO 15002 | DIN 13260-2 | BS 5682 | UNI EN ISO 15001

### Components

Internal body in Chemically nickel-plated aluminum.

External body made of MAKROLON certified for medical use.

AISI 316 stainless steel float.

N.One inlet with standard probe or G 1/4" M RH thread.

N.One G 1/4" M RH or M12x1,25 M RH and 9/16" threaded outlet.

Brass adjuster knob with NYLON 6.6 terminal unit.

EPDM or silicon O-Ring.

Internal graduated rotary meter column and external MAKROLON 2458 certified for medical use polycarbonate column.

1/4 "F PVC bar support.

Medical rubber pipe 6x10

### Technical data

CODE	GAS	INLET CONNECTION	OUTLET CONNECTION	SCALE	BAR
HF144	O <sub>2</sub>	AFNOR NF S 90-116 - 90° - 1,5 m hose	G 1/4" M	0-15 l/min	4,5
HF145	O <sub>2</sub>	DIN 13260-2 - 90° - 1,5 m hose	G 1/4" M	0-15 l/min	4,5
HF146	O <sub>2</sub>	BS 5682 - 90° - 1,5 m hose	G 1/4" M	0-15 l/min	4,5
HF148	Air 400	AFNOR NF S 90-116 - 90° - 1,5 m hose	G 1/4" M	0-15 l/min	4,5
HF149	Air 400	DIN 13260-2 - 90° - 1,5 m hose	G 1/4" M	0-15 l/min	4,5
HF150	Air 400	BS 5682 - 90° - 1,5 m hose	G 1/4" M	0-15 l/min	4,5