



Double flowmeter for oxygen 0-15 l/min



Organismo Notificato n. 0476
Notified Body nr. 0476

Product description

Double variable area flow meter for doubling the single usage, available with 0-15 l/min flow meter; it can be connected to the network by means of couplings AFNOR NF S 90-116, DIN 13260-1, UNI 9507, BS 5682, G thread 1/4" M RH; also available with ABS clamp for instrument bar with specific gas connection; the device enables, by adjusting the needle valve, a flow ranging from 0 to 15 at a pressure of 4.5 bar; flow meter outlet G 1/4" M RH, M12x1,25 M RH or 9/16".

Normatives

NF S 90-116 | UNI 9507 | UNI EN ISO 15002 | DIN 13260-2 | BS 5682 | UNI EN ISO 15001 | SS 8752430

Components

Internal body in Chemically nickel-plated aluminum.

External body made of MAKROLON certified for medical use.

AISI 316 stainless steel float.

N.One inlet with standard probe or G 1/4" M RH thread.

N.One G 1/4" M RH or M12x1,25 M RH and 9/16" threaded outlet.

Brass adjuster knob with NYLON 6.6 terminal unit.

EPDM or silicon O-Ring.

Internal graduated rotary meter column and external MAKROLON 2458 certified for medical use polycarbonate column.

Technical data

CODE	GAS	INLET CONNECTION	OUTLET CONNECTION	SCALE	BAR
HF133	O ₂	G 1/4" M DX	G 1/4" M	0-15 l/min	4,5
HF135	O ₂	AFNOR NF S 90-116	G 1/4" M	0-15 l/min	4,5
HF135M	O ₂	AFNOR NF S 90-116	M 12x1,25 M	0-15 l/min	4,5
HF136	O ₂	DIN 13260-2	G 1/4" M	0-15 l/min	4,5
HF137	O ₂	BS 5682	G 1/4" M	0-15 l/min	4,5