



## Monobloc automatic flaming nozzles

### Product description

The monobloc automatic flaming nozzles are used in automatic flaming and can be installed on either the BS/86 torch or the LITTLE/F torch. The FDT/3-4 nozzles produce a single flame, while the BS/L and BS/T4 nozzles produce multiple flames.



### Technical data

CODE	NOZZLES	TORCH	P O <sub>2</sub>	Q O <sub>2</sub>	P C <sub>3</sub> H <sub>8</sub>	Q C <sub>3</sub> H <sub>8</sub>
M0031EA	BS/L	BS/86	5,5 bar	15,9 Nm <sup>3</sup> /h	1,2 bar	2,5 Nm <sup>3</sup> /h
		LITTLE/F	5,5 bar	14,9 Nm <sup>3</sup> /h	1,2 bar	2,1 Nm <sup>3</sup> /h
M0031C	FDT/3-4	BS/86	2 bar	5,4 Nm <sup>3</sup> /h	0,5 bar	1,2 Nm <sup>3</sup> /h
		LITTLE/F	2 bar	5,4 Nm <sup>3</sup> /h	0,5 bar	1,2 Nm <sup>3</sup> /h
M0031AC	BS/T4	BS/86	4 bar	14 Nm <sup>3</sup> /h	1 bar	2,1 Nm <sup>3</sup> /h
		LITTLE/F	4 bar	14,2 Nm <sup>3</sup> /h	1 bar	2,4 Nm <sup>3</sup> /h