

Food gas equipments



451-type manifold pressure regulator

Product description

Pressure regulator for manifolds, suitable for food-grade gas, equipped with dual pressure gauge to show high and low pressure, used to reduce the pressure down to that of the line or of the equipment. Maximum inlet pressure is 200 bar, the outlet pressure is adjustable up to 12 bar. The gas inlet connection is sW21.7x1/14" 'A', the outlet is fitted with an Ø 8 hose connector. Its maximum nitrogen capacity at 12 bar outlet pressure is 90 Nm³/h, 1500 NI/min.

Normatives

UNI EN ISO 2503 | UNI EN ISO 5171 | Regolamento (CE) n. 1935/2004

Components

Body, cap and overpressure discharge valve integrated in the pressure regulator, made of CW614N chemically nickel-plated brass.

Pressure adjustment by threaded screw.

One W21.7x1/14" F R inlet.

One Ø8 mm hose connector on the outlet.

One 0-315 bar inlet pressure gauge, Ø 60 mm, class 2.5.

One 0-16 bar outlet pressure gauge, Ø 60 mm, class 2.5.

Stainless steel springs.

Food-grade NBR diaphragm.

Silicone O-ring.

Teflon seat.

Nylon gaskets.

Maintenance kit

CODE	DESCRIPTION
HKAL002	REDUCER MAINTENANCE EQ 451 A.P. FOOD

Technical data

CODE	Q max.	P ₁ max.	P ₂ max.	INLET CONNECTION	OUTLET CONNECTION	WEIGHT
HRAL032	90 Nm³/h	200 bar	12 bar	W21,7x1/14" 'A'	Hose connector Ø 8 mm	4.0 kg

Technical Images

