



Nesplon 7

DescriÃ§Ã£o do produto

Nesplon 7 valves are designed to keep the end utilities of industrial gas lines safe; they're fitted with flame arrestors and gas check valves. These valves can be installed directly on the outlet of the pressure reducer; they're suitable for both comburent gas (oxygen) and fuel gas.Nesplon 7 valves have a G3/8" F threaded fitting on the inlet and a G3/8" M fitting on the outlet, with a right-hand thread for oxygen and a left-hand thread for fuel gas.We recommend replacing the Nesplon 7 valves in the case of a flashback, after 5 years from the date of installation and in any case after the time limit of 5 years plus 1 from the manufacturing date on the valve.

Normativos

UNI EN ISO 9539 | UNI EN ISO 5175-1 | UNI 11627


componentes

CW614N brass body and cut-off.
AISI 316 sintered stainless steel flashback arrestor filter.
Stainless steel springs.
Aluminum gaskets.
NBR O-ring.

Dados técnicos

CODE	GAS	Q max.	P max.	INLET CONNECTION	OUTLET CONNECTION
VN7G	FUELS	49,5 Nm³/h	4 bar	G3/8" F L	G3/8" M L
VN7O	COMBURENTS	76,5 Nm³/h	10 bar	G3/8" F R	G3/8" M R

Behringer S.r.l. via Gualco 4, 16165 Genova ITALY
T +39 010 8309103 **F** +39 010 8309183 **e-mail** info@behringer.it **C.F.** e **P.I.** 01167840998



Behringer S.r.l. via Gualco 4, 16165 Genova ITALY
T +39 010 8309103 **F** +39 010 8309183 **e-mail** info@behringer.it **C.F.** e **P.I.** 01167840998